





11四一年时人八人八八八八

ZHUHAI TAICHUAN CLOUD TECHNOLOGY CO., LTD

The 1st Bldg. Taichuan Technopark No. 611 Huawei Road Qianshan Xiangzhou Zhuhai Guangdong China

Tel: +86 756 8665169

Mail: globalmarket@taichuan.com



AITECHNOLOGY

ADVANCED FACE RECOGNIATION ALGORHYTHIM






Mounting



Desk




Gate

Machine




CORE TECHNOLOGY



Accurate HD dual camera has both IR bio-assay and Face recognition function.

Through the advanced dual algorithm get face feature. Accurately recognize correct information, and avoid graphic picture and video image cheating.



Advanced Bio-Assay Algorithm

Taichuan Commercial Face Recognition Access Control system Adopt advanced Bio-Assay Algorithm, could effectively avoid the raider use photo or video to cheating

The IR camera could very efficiently distinguish real face and image on flat picture or video .








Real Person

Photogragh

Video

— Stand —

EXTREME CRAFTMANSHIP



PROJECT SOLUTION






















PROFESSIONAL KIT

Each product exit from factory are including all necessary installation tools and acsessories to save user installation time and cost.



- \bullet Support single device working, no need extreme setting ;
- Support network working, multi devices link by network,
- Support access recording enquiry and security log enquiry.



■ Technical Features

User Qty	1000 User face (Could expanded to 10000 face)
Record Qty	200,000 records
Algorithm	HD Image + Bioassay
Hardware	1.2GHz Quad-Core CPU+ Face Recognition Module
RAM	1GB SDRAM
FLASH	8GB
Camera	IR + HD Dual camera
Verify	Face Recognition , Password, Face+ Password
Verify speed	<1 second
Refused ration	<1%
Fault ration	<0.001%
Key board	Touch Key board ,
Display	7 inch touch screen,1366*768 Resolution
Communication	TCP/IP、Support USB Flash disk
Alarm	Tamper alarm
Access control	Relay access
Lock Support	Support Magnetic lock, Electric blot lock ,
Power Supply	DC 12V-1.5A
Sensing distance	30-80 cm
Working Temp	0°C-40°C
Humidity	20%-80%
Panel Size	116mm*218mm
Installation	Desk , Wall mount, Stand, Gate Machine/Passage way

爭 用户价值

